

Product Datasheet - 21804

Astral 2.0
ID : 21804
Input power : 30W / 50W LED
K-Lite pole top luminaire. Symmetrical / Type II, Type III, Type IV (Asymmetrical light distribution). Luminaire made of Spun aluminium top cover with decorative die cast aluminium knob on top, clear acrylic diffuser. Pressure die cast aluminium supporting arm with base suitable for mounting on Ø60mm OD pipe. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK05. RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : 400mm diameter x 772mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical / Type II, III, IV

Mounting: D2

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey