

Product Datasheet - 21812

Pelican Fort Micro
ID : 21812
Input power : 30W LED
Technical Description
K-Lite pendant mounted compact street light. Symmetrical light distribution. Decorative luminaire made of specially contoured spun aluminium body of high corrosion resistance with a neck design for unique and better aesthetics and external non corrosive stainless steel fasteners. Translucent V acrylic / Translucent convex acrylic diffuser. The mounting arrangement nipple, coupling & Hex nut made of Stainless steel 304 suitable for mounting to internally threaded pipe of designation M30. Protection class IP65. Mechanical resistance IK05. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.9, THD <10%, Surge protection 4KV. Luminaire dimension : 300mm diameter x 290mm / 210mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Pelican Fort Micro
ID : 21812
Holder : E27
Technical Description
K-Lite pendant mounted compact street light. Decorative luminaire made of specially contoured spun aluminium body of high corrosion resistance with a neck design for unique and better aesthetics and external non corrosive stainless steel fasteners. Translucent V acrylic / Clear V acrylic diffuser. The mounting arrangement nipple, coupling & Hex nut made of Stainless steel 304 suitable for mounting to internally threaded pipe of designation M30. Protection class IP65. Mechanical resistance IK05. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey. Prewired with E27 holder and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : 300mm diameter x 290mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: D4

Finish: RAL 9004 Black,RAL 9007 Grey aluminium,RAL 7016 Anthracite grey,Graphite grey