

Product Datasheet - 21815

Karona Fort Mini
ID : 21815
Input power : 30W / 50W LED
Technical Description
K-Lite pendant mounted compact pathway luminaires. TypeII / TypeIII / TypeIV (Asymmetrical light distribution). Decorative luminaire made of specially contoured spun aluminium body of high corrosion resistance with extruded aluminium neck design for unique and better aesthetics and external non corrosive stainless steel fasteners. Convex type clear acrylic diffuser. The mounting arrangement nipple, coupling & Hex nut made of Stainless steel 304 suitable for mounting to internally threaded pipe of designation M30. Protection class IP65. Mechanical resistance IK05. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 72,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : 475mm diameter x 450mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: Type II, Type III, Type IV

Mounting: D4

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey