

Product Datasheet - 21816

Imperial Mini
ID : 21816
Input power : 30W / 50W LED
Technical Description
K-Lite pendant mounted compact street light. Symmetrical Light distribution / Asymmetrical light distribution (Type II / Type III / Type IV). Decorative luminaire made of specially contoured spun aluminium body of high corrosion resistance with a neck design for unique and better aesthetics and external non corrosive stainless steel fasteners. Aluminium casting crown attachment added for aesthetic. Clear V acrylic / Clear polycarbonate diffuser for asymmetrical light & Translucent V acrylic / Translucent convex acrylic diffuser for symmetrical light. The mounting arrangement nipple, coupling & Hex nut made of Stainless steel 304 suitable for mounting to internally threaded pipe of designation M30. Protection class IP65. Pure polyester powder coated RAL 9004 Black & Gold, RAL 9007 Grey aluminium & Gold and RAL 7016 Anthracite grey & Gold, Graphite Grey & Gold. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.9, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : A8 & A9 - 425mm diameter x 401mm height / A10 - 425mm diameter x 285mm height / A12 - 425mm diameter x 431mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Imperial Mini
ID : 21816
Holder : E27
Technical Description
K-Lite pendant mounted compact street light. Decorative luminaire made of specially contoured spun aluminium body of high corrosion resistance with a neck design for unique and better aesthetics and external non corrosive stainless steel fasteners. Aluminium casting crown attachment added for aesthetic. Translucent V acrylic / Clear V acrylic diffuser / Clear polycarbonate diffuser. The mounting arrangement nipple, coupling & Hex nut made of Stainless steel 304 suitable for mounting to internally threaded pipe of designation M30. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey. Prewired with E27 holder and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : A8 & A9 - 425mm diameter x 401mm height / A12 - 425mm diameter x 431mm height.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: Type II / Type III / Type IV / Symmetrical

Mounting: D4

Finish: RAL 9004 Black & Gold,RAL 9007 Grey aluminium & Gold,RAL 7016 Anthracite grey & Gold,Graphite grey & Gold