

Product Datasheet - 22520

Carley Round 2.0 - Column Light
ID : 22520
Input power : 40W LED
Technical Description
K-Lite Column Light designed for surface mounted. Beam angle 40°. Luminaire made of Ø166mm extruded aluminium alloy (grade 6063) with die-cast aluminium components of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass. Die cast aluminium mounting plate 300mm dia x 12mm thick with 4 elongated holes 38 x 19 to suit M16 bolts at CC180. This mounting plate along with foundation bolts of suitable size to be used for ensuring firm grouting into the specially designed foundation. PDC aluminium service door 348mm height x 110mm width shall be provided with the company logo embossed on the bottom of the door. The control gear tray is prewired with 2.5 Sq.mm cable, 6A SP MCB and 32A Ramanuj stud type 4 way terminal block for loop-in / loop-out arrangement, 5A 2 Way terminal connector and provision for earthing. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K. Colour rendering index (CRI)90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 300mm diameter x 3500mm / 4000mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 40

CCT: 2700K,3000K,4000K,6500K

Optics: 40°

Mounting: M11

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey