

Product Datasheet - 22522

Cyrilla Bollard
ID : 22522
Input power : 12W LED
Technical Description
K-Lite Bollard luminaire designed for surface mounted. Symmetrical light distribution. Luminaire made of extruded aluminium supporting arm (grade 6063), die cast aluminium top and bottom frame and external non corrosive stainless steel fasteners. Bespoke laser cutting design options. Die cast aluminium mounting plate 101mm square x 4mm thick with 4 elongated holes 22 x 10 to suit M8 bolts at PCD 60 with pure polyester powder coating. This mounting plate along with foundation bolts of suitable size to be used for ensuring firm grouting into the specially designed foundation. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey & Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K. Colour rendering index (CRI)90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 206mm square x 360mm / 500mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 12

CCT: 2700K,3000K,4000K,6500K

Optics:

Mounting: M37

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey