

## Product Datasheet - 22551

lyra Mini<br>ID : 22551<br>Input power : 15W<br>Technical Description<br>K-Lite compact and robust flood light luminaire designed to provide uniform illumination in open spaces. Beam angle 12° / 24° / 40°. Luminaire made of aluminium of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass. Adjustable bracket made of die cast aluminium. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K (RGBW on request), Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD< 10%, Surge protection 4KV. Luminaire dimension : 128mm length x 114mm diameter x 209mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 15

CCT: 2700K,3000K,4000K,5700K

Optics: 12°,24°,40°

Mounting: M56

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey