

Product Datasheet - 22562

Wall Grazer - Linear In-Ground Luminaire
ID : 22562
Input power : 12W / 24W

LED
Technical Description
K-Lite compact and minimalist linear recess mounted designed for floor mount. Beam angle 100°. Luminaire made of extruded aluminium alloy of high corrosion resistance, stainless steel top ring (grade 316) and external non corrosive stainless steel fasteners. Powder coated aluminium profile installation housing for preparing the recess opening in ground. Optical compartment closed at the top with translucent toughened glass of 6mm thickness. Protection class IP67. Mechanical resistance IK05. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Constant voltage non integral power supply at 24Vdc assures safety. Luminaire dimension : 310mm / 550mm / 1025mm length x 68mm width x 83mm height. Luminaire installation in a recessed opening cut-out dimension : 300mm / 540mm / 1015mm length x 68mm width x 80mm height. CE & BIS Certified.

Inhouse NABL accredited lab.

Wall Washer - Linear In-Ground Luminaire
ID :

22562
Input power : 12W / 24W / 48W LED
Technical Description
K-Lite compact and minimalist linear recess mounted designed for floor mount. Beam angle 8° / 12° / 24° / 40° / 60° / Elliptical. Luminaire made of extruded aluminium alloy of high corrosion resistance, stainless steel top ring (grade 316) and external non corrosive stainless steel fasteners. Powder coated aluminium profile installation housing for preparing the recess opening in ground. Optical compartment closed at the top with clear toughened glass of 6mm thickness. Protection class IP67. Mechanical resistance IK05. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Constant voltage non integral power supply at 24Vdc assures safety. Luminaire dimension : 310mm / 550mm / 1025mm length x 68mm width x 83mm height. Luminaire installation in a recessed opening cut-out dimension : 300mm / 540mm / 1015mm length x 68mm width x 80mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: Recess

Finish: SS Front Cover