

Product Datasheet - 22566

Quad Mini
ID : 22566
Input power : 6W / 12W / 18W LED
Technical Description
K-Lite ceiling mounted compact downlight. Beam angle 12° / 24° / 40°. Luminaire made of extruded aluminium (grade 6063) 100 Square x 3mm thickness, pressure die-cast aluminium alloy of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass of 4mm thickness. Polycarbonate optical lens. Aluminium mounting clamp for surface mounting on ceiling. Single cable entrance via M10 cable gland. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, Surge protection 4KV. Luminaire dimension : 100mm square x 130mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,6500K

Optics: 12°, 24°,40°

Mounting: Surface

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey