

Product Datasheet - 22569

Elina
ID : 22569
Input power : 1 x 6W / 2 x 6W LED
Technical Description
K-Lite Bollard luminaire designed for surface mounted. Beam angle 120°. Luminaire made of extruded aluminium tube (grade 6063) and non corrosive stainless steel fasteners. PMMA diffuser. Pressure die cast aluminium mounting base Ø130 x 37mm height with 3 holes Ø7 to suit coach screws at PCD110 with pure polyester powder coating. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K. Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Constant voltage non integral power supply at 24Vdc assures safety. Luminaire dimension : Single arm - 184mm Length x 130mm diameter x 1000mm height / Double arm - 245mm Length x 130mm diameter x 1000mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: 120°

Mounting: M57

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey