

Product Datasheet - 22782

Nebula
ID : 22782
Input power : 18W LED
Technical Description
K-Lite Spike / Bracket mounted compact spot light designed to provide directional light. Beam angle 12° / 24° / 40°. Luminaire made of extruded aluminium section with inner grooves to fix the top and bottom ring (grade 6063) Ø100 x 2.5mm thickness, pressure die cast aluminium top and bottom ring of high corrosion resistance and external non corrosive A2 stainless steel fasteners. Clear toughened glass of 4mm thickness. Polycarbonate optical lens. Surface mounting spike made of polypropylene black / Pressure die-cast aluminium surface mounting base. Swivel range of 0° - 90°. Single cable entrance M10 cable gland. Protection class IP66. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : Spike - 163mm length x 104mm width x 544mm height / Bracket- 163mm length x 104mm width x 194mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 18

CCT: 2700K,3000K,4000K,6500K

Optics: 12°,24°,40°

Mounting: M56

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey