

Product Datasheet - 22797

Torch Stix
ID : 22797
Input power : 1 x 6W / 2 x 6W LED
Technical Description
K-Lite Bollard luminaire designed for surface mounted. Optical beam angle 12° / 24° / 40°. Luminaire made of extruded aluminium tube (grade 6063) of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass. Pressure die cast aluminium mounting base Ø130 x 37mm height with 3 holes Ø7 to suit coach screws at PCD110. Protection class IP65. Mechanical resistance IK06. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K. Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : Single Arm - 200mm length x 142mm width x 1000mm height / Double Arm - 254mm length x 157mm width x 2000mm height . CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,6500K

Optics: 12°,24°,40°

Mounting: M57

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey