

Product Datasheet - 22807

Luna Midi - Street
ID : 22807
Input power : 30W / 50W LED
Technical Description
K-Lite Side mounted pole top luminaire. Type II / Type III / Type IV (Asymmetrical light distribution). Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass. Polycarbonate optical lens. Gravity die cast aluminium mounting base suitable for mounting 60mm OD pipe. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : 513mm length x 350mm width x 177mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30W / 50

CCT: 3000K,4000K,5700K

Optics: Type II / Type III / Type IV

Mounting: D2

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey