

Product Datasheet - 22809

Lucy 2.0
ID : 22809
Input power : 30W / 50W LED
Technical Description
K-Lite Post top luminaire. Symmetrical light distribution. Luminaire body made of die cast aluminium with die-cast aluminium components of high corrosion resistance and external non corrosive stainless steel fasteners. Aluminium base suitable for mounting Ø76mm OD pipe. Clear polycarbonate diffuser. Protection class IP66. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : 176mm diameter x 551mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical

Mounting: D3

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey