

Product Datasheet - 23265

Form-17 - Linear Lighting
ID : 23265
Input power : 5W/10W/15W/20W/30W/40W

LED
Technical Description
K-Lite compact and minimalist linear surface mounted designed for ceiling / Floor / surface mount. Beam angle 120°(Pixelated). Luminaire made of extruded aluminium alloy (grade 6063) of high corrosion resistance and non corrosive stainless steel fasteners. Polyurethane encapsulation diffuser. IP67 connector on both ends and can be easily installed via mounting clip or adjustable wall clamp. Protection class IP67. Mechanical resistance IK07. Powder coated RAL 9004 Black, RAL9016 Traffic white, Anodised Aluminium. Available colour temperature 2700K / 3000K / 4000K / RGBW / RGBW Pixel, Colour rendering index (CRI)>90. SDCM = 3 MacAdam. K-Lite LED module with expected service life of at least 60,000 operating hours. Constant voltage non integral power supply at 24Vdc assures safety. Luminaire dimension : 510mm/1010mm/1510mm/2010mm length x 17mm width x 9mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,RGBW,RGBW Pixel

Optics:

Mounting:

Finish: Anodized Aluminium