

Product Datasheet - 23627

Wall Torch
ID : 23627
Input power : 1 x 6W LED / 2 x 6W LED
Technical Description
K-Lite Wall-mounted compact downlight. Optical beam angle 12° / 24° / 40°. Luminaire made of extruded aluminium (grade 6063) of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass. Pressure die cast aluminium base for surface mounting on wall. Protection class IP65. Mechanical resistance IK06. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K. Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : 1 x 6W LED - 73mm length x 51mm diameter x 148mm height / 2 x 6W LED - 73mm length x 51mm diameter x 175mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,6500K

Optics: 12°,24°,40°

Mounting: W32

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey