

Product Datasheet - 24035

Torch ID : 24035
Input power : 6W LED
Technical Description
K-Lite ceiling mounted compact downlight. Optical beam angle 12 ° / 24° / 40°. Luminaire made of extruded aluminium (grade 6063) of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass. Mounting clamp for surface mounting on ceiling / 1m Suspension Kit for pendant mounting on ceiling. Protection class IP65. Mechanical resistance IK06. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)> 90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : 50.8mm diameter x 203mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 6

CCT: 2700K,3000K,4000K,6500K

Optics: 25°,40°,15°

Mounting:

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey