

Product Datasheet - 24251

Stencil Pro - Column Light
ID : 24251
Input power : 40W LED
Technical Description
K-Lite Column Light designed for surface mounted. Beam angle 120°. Luminaire made of extruded aluminium (grade 6063) with Supporting arms made of gravity die-cast aluminium. Satin acrylic diffuser. Die-cast aluminium mounting plate 250mm diameter x 12mm thick with 4 elongated holes 38 x 19 to suit M16 bolts at CC140. This mounting plate along with foundation bolts of suitable size to be used for ensuring firm grouting into the specially designed foundation. PDC aluminium service door 348mm height x 81mm width shall be provided with the company logo embossed on the bottom of the door & vandal resistant Loss proof screw. The control gear tray is prewired with 2.5 Sq.mm cable, 6A SP MCB and 32A Ramanuj stud type 4 way terminal block for loop-in / loop-out arrangement, 5A 2 Way terminal connector and provision for earthing. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 50,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 5KV. Luminaire dimension : 730mm length x 3000mm height / 730mm length x 4000mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 40

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical

Mounting: M15

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey