

Product Datasheet - 24262

Corvus Hybrid
ID : 24262
Input power : 12W LED
Technical Description
K-Lite compact spot light luminaire designed for spike mounting. Symmetrical light distribution. Luminaire made of extruded aluminium (grade 6063), pressure die-cast aluminium top cover and external non corrosive stainless steel fasteners. Clear toughened glass of 4mm thickness. Surface mounting spike made of polypropylene black. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K. Colour rendering index (CRI)90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.90, THD <10%, Surge protection 3KV. Luminaire dimension : 210mm diameter x 493mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 12

CCT: 2700K,3000K,4000K,6500K

Optics:

Mounting:

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey