

Product Datasheet - 24306

Waco Pro Midi
ID : 24306
Input power : 120W LED
Technical Description
K-Lite Side / Top mounted pole top luminaire. Type II (Asymmetrical light distribution). Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass. Protection class IP66. Mechanical resistance IK08. RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K, 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. SDCM-5 MacAdam. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.97, THD <10%, Surge protection 6KV. Suitable for mounting on to 60 mm dia pipe at lateral (side entry) and vertical (top mount) and adjustable angle -15° to +15°. Luminaire dimension : 645mm length x 257mm width x 147mm height. For mounting heights of 6000 - 8000mm. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 120

CCT: 2700K,3000K,4000K,5700K

Optics: Type II

Mounting: D12

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey