

Product Datasheet - 24327

Leva-2-18
ID : 24327
Input power : 180W LED
Technical Description
K-Lite compact and minimalist linear surface mounted designed for wall, Ceiling & floor mount. Beam angle 20°. Luminaire made of aluminium alloy (grade 6063), aluminium flush end caps of high corrosion resistance and non corrosive stainless steel fasteners. Mounting bracket with an adjustable feature to facilitate proper aiming of the luminaire at desired angle. Optical compartment closed at the top with clear toughened glass. RAL 7024 Graphite grey colour finish. Luminaire power cord for single colour 2 x 1.0mm² rubber wire of 0.5 metre length / RGBW signal wire 5 x 0.5mm² rubber wire male female butt joint unilateral 0.5mm length. Protection class IP66. Mechanical resistance IK05. Available colour temperature RGBW / 3000K (Other CCT's on request), Colour rendering index (CRI)>80. SDCM-3 MacAdam. K-Lite LED module with expected service life of at least 50,000 operating hours. Constant voltage non integral power supply at 24Vdc assures safety. Luminaire dimension : 1000mm length x 120mm width x 162mm height. Inhouse NABL accredited lab.

Wattage: 180

CCT: 3000K,RGBW

Optics: 20°

Mounting: Surface

Finish: RAL 7024 Graphite Grey