

## Product Datasheet - 24328

Waco Pro Mini  
ID : 24328  
Input power : 60W LED  
Technical Description  
K-Lite Side & top mounted pole top luminaire. Type II (Asymmetrical light distribution). Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass. Protection class IP66. Mechanical resistance IK09. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey & Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. SDCM-5 MacAdam. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.97, THD <10%, Surge protection 6KV. Suitable for mounting on to 60mm dia pipe at lateral (side entry) and vertical (top mount) and adjustable angle -15° to +15°. Luminaire dimension : 555mm length x 210mm width x 143mm height. For mounting heights of 4000 -6000mm. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 60

CCT: 2700K,3000K,4000K,5700K

Optics: Type II

Mounting: D12

Finish: RAL 9004 Signal black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey