

Product Datasheet - 24387

Luna-7
ID : 24387
Input power : 50W / 100W LED
Technical Description
K-Lite Post top luminaire. Type II, Type III, Type IV (Asymmetrical light distribution). Decorative luminaire made of pressure die cast aluminium body of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass of 5mm thickness. The module have polycarbonate optical lens with aluminium heatsink for thermal management. Slight regress in the optical assembly for better glare control. Gravity die cast aluminium mounting base suitable for mounting 60mm OD pole. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 490mm diameter x 582mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 3000K, 4000K, 5700K

Optics: Type II/Type III/Type IV

Mounting: D2

Finish: RAL 9004 Black, RAL 9007 Grey Aluminium, RAL 7016 Anthracite Grey