

Product Datasheet - 24389

Line
ID : 24389
Input power : 30W LED - Single Arm / 60W LED - Double Arm
Technical Description
K-Lite Pole top luminaire. Type III Medium (Asymmetrical light distribution). Luminaire made of Extruded aluminium alloy (grade6063) of high corrosion resistance. Polycarbonate optical lens. Extruded aluminium base suitable for mounting 76mm OD pole / 72mm Square pole. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : Single Arm - 640mm length x 94mm width x 324mm height / Double Arm - 1280mm length x 94mm width x 324mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 3000K,4000K,5700K

Optics: Type III Medium

Mounting: D3,D15

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey