

Product Datasheet - 24390

Palma
ID : 24390
Input power : 50W / 100W LED
Technical Description
K-Lite Pole top luminaire. Type III (Asymmetrical light distribution). Luminaire made of aluminium of high corrosion resistance. Reflector system made of polycarbonate (matte white). Polycarbonate optical lens. Extruded aluminium base suitable for mounting 76mm / 88.9mm OD & 91mm Square pole. All external screws are made of stainless steel. Protection class IP65 for LED Module. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension :868mm length x 249mm width x 300mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 50W,100

CCT: 2700K,3000K,4000K,5700K

Optics: Type III

Mounting: D26

Finish: RAL 9004 Signal black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey