

## Product Datasheet - 24391

Avenue 40<br>ID : 24391<br>Input power : 40W LED<br>Technical Description<br>K-Lite Side mounted pole top luminaire. Type II (Asymmetrical light distribution). Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass. Protection class IP66. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. SDCM-3 MacAdam. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.97, THD <10%, Surge protection 4KV. Suitable for mounting on to 38 mm dia pipe at lateral (side entry). Luminaire dimension : 378mm length x 120mm width x 72mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 40

CCT: 2700K,3000K,4000K,5700K

Optics: Type II

Mounting: D6

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey