

Product Datasheet - 24440

Navya Mini
ID : 24440
Input power : 24W LED
Technical Description
K-Lite Pole top luminaire. Type III Medium (Asymmetrical light distribution). Luminaire made of aluminium & extruded aluminium alloy (grade 6063) of high corrosion resistance. Polycarbonate optical lens. Extruded aluminium base suitable for mounting 72mm & 91mm square pole. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK10. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 333mm / 353mm length x 303mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 24

CCT: 2700K,3000K,4000K,5700K

Optics: Type III Medium

Mounting: D15,D16

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey