

## Product Datasheet - 24452

Moon Ring<br>ID : 24452<br>Input power : 200W LED<br>Technical Description<br>K-Lite Post top luminaire. Symmetrical light distribution. Decorative luminaire made of aluminium of high corrosion resistance and non corrosive stainless steel fasteners. The module have polycarbonate optical lens with extruded aluminium heatsink for thermal management with vertical fin design for longer life of the LEDs. Extruded aluminium pipe (grade 6063) suitable for mounting 88.9mm OD pole. Protection class IP65 LED module, Mechanical resistance IK09. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 764mm diameter x 571mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 200

CCT: 3000K,4000K,5700K

Optics: Symmetrical

Mounting: D26

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey