

Product Datasheet - 24554

Stix Light
ID : 24554
Input power : 3W LED
Technical Description
K-Lite Bollard luminaire designed for surface / earth spike mounted. Symmetrical light distribution. Luminaire made of extruded aluminium tube and external non corrosive stainless steel fasteners. Clear acrylic rod. Pressure die cast aluminium mounting base 60mm diameter x 18mm with 2 holes Ø6.5 to suit coach screws at PCD 41 with pure polyester powder coating. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K (Special CCT on Request- Amber / Red / Greed / Blue). Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : Surface mount - 60mm diameter x 762 / 962 / 1162 mm height & Spike Mount - 99mm x 59mm x 1100 / 1300 / 1500mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 3

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: M54

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey