

Product Datasheet - 24560

Pyro Stix Light
ID : 24560
Input power : 6W LED
Technical Description
K-Lite Bollard luminaire designed for surface / Spike mounted. Symmetrical light distribution. Luminaire made of stainless steel pipe (grade 304) & Pressure die cast aluminium pyro top and non corrosive stainless steel fasteners. Clear acrylic diffuser. Surface mounting spike made of polypropylene / Die cast aluminium mounting base 60mm diameter with 2 holes 6.5mm diameter to suit coach screws at PCD 41 with cable entry hole 8.5mm diameter. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K. Colour rendering index (CRI)>80. Constant voltage non integral power supply at 24Vdc assures safety. Supplied with suitable external dc to dc converter, to be installed with suitable IP Junction box. Luminaire dimension : Surface mount : Ø128 x 500, Ø128 x 700, Ø128 x 900 mm height / Spike mount : Ø128 x 800, Ø128 x 1000, Ø128 x 1200 mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 6

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical

Mounting:

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey