

Product Datasheet - 24735

Verbena Bollard
ID : 24735
Input power : 12W LED
Technical Description
K-Lite Bollard luminaire designed for surface mounted. Symmetrical light distribution. Luminaire made of square extruded aluminium tube, aluminium components and non corrosive stainless steel fasteners. Inner toughened glass. Bespoke laser cutting design options. Pressure die cast aluminium mounting plate 150 square x 4mm thick with 3 elongated holes 20 x 12 to suit M10 bolts at PCD 90. The base plate have a cable entry hole of 35mm dia at the center. This mounting plate along with foundation bolts of suitable size to be used for ensuring firm grouting into the specially designed foundation. Protection class IP65. Mechanical resistance IK10. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K. Colour rendering index (CRI)90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 150mm square x 1000mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 12

CCT: 2700K,3000K,4000K,6500K

Optics: Symmetrical

Mounting: M36

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey