

Product Datasheet - 24849

Zucchini
ID : 24849
Input power : 30W LED
Technical Description
K-Lite Post top luminaire. Symmetrical light distribution. Luminaire made of extruded aluminium alloy (grade 6063) with gravity die cast aluminium top closing cover and glass fixing ring of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass. Gravity die-cast aluminium bracket with base suitable for mounting Ø50mm OD pipe. Protection class IP65. Mechanical resistance IK06. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K. Colour rendering index (CRI)>70. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >88%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 176mm diameter x 598mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30

CCT: 2700K,3000K,4000K,5700K

Optics: 120°

Mounting: D1

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey