

## Product Datasheet - 24932

Magudam Midi<br>ID : 24932<br>Input power : 30W LED<br>Technical Description<br>K-Lite pole-top luminaire. Symmetrical light distribution. Luminaire made of spun aluminium, die cast aluminium and non corrosive stainless steel fasteners. Pressure die cast aluminium magudam attachment added for aesthetics. Translucent acrylic diffuser. Die cast aluminium base suitable for mounting on Ø50 mm OD pipe. Pure polyester powder coated RAL 9004 Black & Gold, RAL 9007 Grey aluminium & Gold, RAL 7016 Anthracite grey & Gold, Graphite grey & Gold. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. SDCM-3 MacAdam. K-Lite LED module with expected service life of at least 50,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.90, THD <10%, Surge protection 4KV. Luminaire dimension : 367mm diameter x 647mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: D1

Finish: RAL 9004 Black & Gold, RAL 9007 Grey aluminium & Gold, RAL 7016 Anthracite grey & Gold, Graphite grey & Gold