

Product Datasheet - 24941

Honeydrop
ID : 24941
Input power : 150W LED
Technical Description
K-Lite pendant mounted compact street light luminaire. Type II / Type III / Type IV (Asymmetrical light distribution). Luminaire made of die cast aluminium featuring high strength and anti corrosion and external non corrosive stainless steel fasteners. Convex type clear toughened glass. The mounting arrangement nipple, coupling & Hex nut made of Stainless steel 304 suitable for mounting to internally threaded pipe of designation M30. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 72,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 512mm diameter x 805mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 150

CCT: 3000K,4000K,5700K

Optics: Type II,Type III,Type IV

Mounting: D4

Finish: RAL 9004 Black,RAL 9007 Grey aluminium,RAL 7016 Anthracite grey,Graphite grey