

Product Datasheet - 25040

Juno
ID : 25040
Input power : 60W LED
Technical Description
K-Lite pole top luminaire. Beam angle 120°. Luminaire made of spun aluminium, integrated with extruded aluminium pipe along with pressure die cast aluminium base through supporting arms made of gravity die cast aluminium and non corrosive stainless steel fasteners. Diffuser placed into the provision formed on the periphery of the bottom cover. Translucent acrylic diffuser. Suitable for mounting on Ø60mm OD pipe. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >88%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 600mm diameter x 443mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 60

CCT: 2700K,3000K,4000K,5700K

Optics: 120°

Mounting: D2

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey