

Product Datasheet - 26789

Aston 2
ID : 26789
Input power : 2 x 60W LED
Technical Description
K-Lite high efficiency flood light luminaire designed to provide uniform illumination in open spaces. Beam angle 12° / 25° / 40° / 60°. Extruded aluminium side frame, IP67 LED Module with excellent thermal management heat sink & polycarbonate optical lens. Mounting bracket made of CRCA sheet (3mm thickness). Luminaire supplied with fast IP68 connectors. All external screws are made of stainless steel. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K / Amber(25°). Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 84,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >90%, Power factor >0.98, THD< 6.5%, Surge protection 4KV. Luminaire dimension : 342mm length x 135mm width x 245mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 60

CCT: 3000K,4000K,5700K,Amber(25°)

Optics: 60°,40°,25°,12°

Mounting: Surface

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey